

## 热收缩连续母排保护套管 Heat Shrinkable Continuous Busbar Protection Casing

### 使用说明 Directions for use

- ① 起始收缩温度70℃，全部回缩温度≤125℃。由于母排管均较厚，在120℃以下加热收缩太慢，建议客户使用时用热风枪均匀加热收缩或在120℃以上烘箱内加热收缩；
- ② 适用温度范围：-40~125℃；
- ③ 使用率≤10%；
- ④ 环保热收缩母排保护套管产品均符合欧盟RoHS指令。

- ① The initial shrinkage temperature to 70°C, all bounce back temperature 125°C or less. Due to the busbar tube are thicker, under 120°C heat shrink too slow, suggest customers to use when use hot Air pressure gun uniform heating or above 120°C oven heating contraction;
- ② The applicable temperature range: -40~125°C;
- ③ Utilization of 10% or less;
- ④ Environmental protection heat-shrinkable busbar protection casing products comply with the eu RoHS directive.

### 产品颜色 Product color

铁红、黄、绿、黑色，可按客户要求生产其他颜色。

Iron oxide red, yellow, green, black, other colors can produce according to customer's request.

### 10KV热缩连续母排保护套管产品的规格尺寸（10KV WMPG系列）

10 kv busbar protection casing for heat shrinkable products specification size (10 kv WMPG series)

型号	使用母排宽度	内径 (mm)	壁厚 (mm)(S)	内径 (mm)	壁厚 (mm)(L)	标准包装 (米/盘)
10KV WMPG 15/6	12/15	15±0.8	1.0±0.2	≤6	2.5±0.2	25
10KV WMPG 20/8	20/15	20±0.8	1.0±0.2	≤8	2.5±0.2	25
10KV WMPG 25/10	25/18	25±0.8	1.0±0.2	≤10	2.5±0.2	25
10KV WMPG 30/12	30/20	30±0.8	1.0±0.2	≤12	2.5±0.2	25
10KV WMPG 40/16	40/30	40±1.0	1.2±0.2	≤16	2.8±0.3	25
10KV WMPG 50/20	50/35	50±2.0	1.2±0.2	≤20	2.8±0.3	25
10KV WMPG 60/24	60/45	60±3.0	1.2±0.2	≤24	2.8±0.3	25
10KV WMPG 65/26*	65/45	65±3.0	1.2±0.3	≤26	2.8±0.3	25
10KV WMPG 70/28	70/50	70±3.0	1.2±0.3	≤28	2.8±0.3	25
10KV WMPG 75/30*	75/50	75±3.0	1.2±0.3	≤30	2.8±0.3	25
10KV WMPG 80/32	80/55	80±3.0	1.2±0.3	≤32	2.8±0.3	25
10KV WMPG 85/34*	80/65	85±3.0	1.2±0.3	≤34	2.8±0.3	25
10KV WMPG 100/40	100/75	100±4.0	1.2±0.3	≤40	2.8±0.3	25
10KV WMPG 120/48	120/85	120±4.0	1.2±0.3	≤48	2.8±0.3	25
10KV WMPG 150/60	150/105	150±4.0	1.2±0.3	≤60	2.8±0.3	25
10KV WMPG 160/64*	150/	160±4.0	1.2±0.3	≤64	2.8±0.3	25
10KV WMPG 180/72	180/120	180±5.0	1.2±0.3	≤72	2.8±0.3	25
10KV WMPG 210/84*	210/140	210±5.0	1.2±0.3	≤84	2.8±0.3	25
10KV WMPG 230/92*	230/150	230±5.0	1.2±0.3	≤92	2.8±0.3	25

说明：1、适用母排规格中20/15表示适用于20MM宽的矩形母排或直径为15MM的圆形母排。

2、带\*号的规格上做库存，需要下订单特殊定做。

Description: 1、suitable bus specification applies to 20 mm wide for the 20/15 in rectangle busbar or 15 mm diameter circular bus.

2、\* on the specifications of the inventory, need special customized orders.



### 35KV热缩连续母排保护套管产品的规格尺寸（35KV WMPG系列）

35 kv busbar protection casing for heat shrinkable products specification size (35 kv WMPG series)

型号	使用母排宽度	内径 (mm)	壁厚 (mm)(S)	内径 (mm)	壁厚 (mm)(L)	标准包装 (米/盘)
35KV WMPG 30/15	30	30±1.0	1.9±0.5	15	4.0±0.3	15
35KV WMPG 35/18	30/40	35±1.0	1.9±0.5	18	4.0±0.3	15
35KV WMPG 40/20	40	40±1.0	1.9±0.5	20	4.0±0.3	15
35KV WMPG 50/25	50	50±2.0	1.9±0.5	25	4.0±0.3	15
35KV WMPG 60/30	60	60±2.0	1.9±0.5	30	4.0±0.3	15
35KV WMPG 65*/33	60/70	65±2.0	1.9±0.5	33	4.0±0.3	15
35KV WMPG 80/35	70	70±2.0	1.9±0.5	35	4.0±0.3	15
35KV WMPG 86/38*	70/80	75±2.0	1.9±0.5	38	4.0±0.3	15
35KV WMPG 90/40	80/100	80±3.0	1.9±0.5	40	4.0±0.3	15
35KV WMPG 200/50	100/120	100±4.0	1.9±0.5	50	4.0±0.3	15
35KV WMPG 120/60	150	120±4.0	1.9±0.5	60	4.0±0.3	15
35KV WMPG 150/75	180	150±4.0	1.9±0.5	75	4.0±0.3	15
35KV WMPG 180/90*	MAX	185±4.0	1.9±0.5	90	4.0±0.3	15
35KV WMPG 210/105*	MAX	210±4.0	1.9±0.5	105	4.0±0.3	15
35KV WMPG 230/115*	MAX	230±4.0	1.9±0.5	115	4.0±0.3	15

说明：带\*号的规格上做库存，需要下订单特殊定做。

Description: with \* on the specifications of the inventory, need special customized orders.

● 特殊尺寸可订制 Special size can be customized